

ABCO Bead COMPONENTS

EDMC060303-NQ Series



5448-4, Sangdaewon-dong, Jungwon-gu,
Seongnam-si, Gyeonggi-do, KOREA

Sales Dept. TEL:82-31-730-5082

FAX:82-31-730-5152

Eng. Dept. TEL:82-31-730-5053

FAX:82-31-730-5153

ABCO ELECTRONICS CO., LTD.

EDMC060303-NQ Series



<http://www.abco.co.kr>

▣ Features

1. This specification applies to MULTILAYER FERRITE CHIP BEADS
2. Operating temperature -55°C ~ +125°C. (Including self - temperature rise)

▣ Ordering Code

EDMC	060303	T	-	100	Y	-	NQ
①	②	③		④	⑤		⑥

① Type	
EDMC	

② Dimensions(mm)	
060303 : 0.6(L) × 0.3(W) × 0.3(T)	

③ Packing	
T	TAPING

④ Impedance(Ω)	
100	10
121	120

⑤ Tolerance	
Y : ±25%	


⑥ Internal Code	
NQ	

EDMC060303-NQ Series




<http://www.abco.co.kr>

■ Shapes and Dimensions



■ Recommended PC Board Pattern



Series	A(mm)	B(mm)	C(mm)	D(mm)
EDMC060303-NQ	0.6±0.03	0.3±0.03	0.3±0.03	0.15±0.05

L(mm)	G(mm)	H(mm)
0.2~0.3	0.75~1.05	0.3

■ Electrical Characteristics

Part Number	Impedance ($\Omega \pm 25\%$)	Test Frequency (MHz)	RDC (Ω) Max.	Rated Current(mA)
				$\Delta T = 30^\circ\text{C}$ Max.
EDMC060303T-100Y-NQ	10	100	0.4	300
EDMC060303T-220Y-NQ	22	100	0.5	200
EDMC060303T-470Y-NQ	47	100	0.7	200
EDMC060303T-750Y-NQ	75	100	1.0	200
EDMC060303T-121Y-NQ	120	100	1.5	100

1. Testing Instrument

- Impedance : HP4291A
- RDC : HP4338B or CHEN HWA 502

2. Rate Current : Applied the current to coils, the temperature rise shall not be more than 30°C

EDMC060303-NQ Series



<http://www.abco.co.kr>

■ Graph

