


LPF1280 SERIES



<http://www.abco.co.kr>

LPF1280 SERIES

■ SHAPE & DIMENSIONS / RECOMMENDED SOLDER LAND PATTERN Unit:mm



* Marking : White

■ ELECTRICAL CHARACTERISTICS

() is typical value.

Ordering code	Inductance [μ H]	Tolerance (%)	F (kHz)	Rdc Max. (Ω)	I _{d1} Max. (A)	I _{d2} Typ. (A)
LPF1280T - 1R0M	1.0	± 20	100	0.007	12.00	13.03
LPF1280T - 2R4M	2.4	± 20		0.013	10.00	10.38
LPF1280T - 3R5M	3.5	± 20		0.014	9.30	9.69
LPF1280T - 4R7M	4.7	± 20		0.015	9.10	8.69
LPF1280T - 5R8M	5.8	± 20		0.019	8.60	7.56
LPF1280T - 6R8M	6.8	± 20		0.022	8.30	7.30
LPF1280T - 8R2M	8.2	± 20		0.020	8.00	7.02
LPF1280T - 100M	10.0	± 20		0.022	6.70	6.87
LPF1280T - 150M	15.0	± 20		0.026	5.65	6.50
LPF1280T - 220M	22.0	± 20		0.036	4.70	5.79
LPF1280T - 330M	33.0	± 20		0.054	3.90	5.31
LPF1280T - 470M	47.0	± 20		0.087	3.25	3.50
LPF1280T - 530M	53.0	± 20		0.090	3.10	3.30
LPF1280T - 680M	68.0	± 20		0.110	3.00	3.20
LPF1280T - 101M	100.0	± 20		0.140	2.10	2.62
LPF1280T - 151M	150.0	± 20		0.200	1.80	2.30
LPF1280T - 221M	220.0	± 20		0.320	1.45	1.97
LPF1280T - 251M	250.0	± 20		0.375	1.40	1.59
LPF1280T - 271M	270.0	± 20		0.400	1.35	1.74
LPF1280T - 331M	330.0	± 20		0.450	1.20	1.65
LPF1280T - 471M	470.0	± 20		0.690	1.00	1.40
LPF1280T - 561M	560.0	± 20		0.810	0.92	0.92
LPF1280T - 681M	680.0	± 20		0.900	0.90	0.82
LPF1280T - 821M	820.0	± 20		1.170	0.72	0.80
LPF1280T - 102M	1000.0	± 20		1.450	0.70	0.77
LPF1280T - 152M	1500.0	± 20		1.950	0.65	0.65
LPF1280T - 222M	2200.0	± 20		2.690	0.55	0.57
LPF1280T - 332M	3300.0	± 20		4.560	0.35	0.40
LPF1280T - 103M	10000.0	± 20		16.000	0.22	0.22

▼ Test Equipments

- Inductance measured : Agilent E4980A Precision LCR Meter or equivalent(100kHz, 0.5V)
- Rdc : HIOKI 3540 m Ω HiTESTER or equivalent
- I_{d1}(The saturation current) : $\Delta L \leq 20\%$ reduction from initial L value
Agilent 4284A LCR Meter + Agilent 42841A Bias Current Source
- I_{d2}(The temperature rise) : $\Delta T = 40^\circ\text{C}$ typical at rated DC current
Yokogawa DR130 Hybrid Recorder + Agilent 6692A DC Power Supply

* Rated DC current(I_d) : The value of I_{d1} or I_{d2} , whichever is smaller

▼ Operating Temperature Range

-40 ~ +125°C (Including self-generated heat)