



# ACM-A3637 Metal Alloy Low-Resistance Resistor Product Specifications (Automotive Grade)

Document No.	IE-SP-174
Released Date	2020/01/10
Page No.	1

## 1 Scope:

- 1.1 This specification is applicable to lead free and halogen free of RoHS directive for ACM-A3637 4 terminals metal alloy low-resistance resistor.
- 1.2 This product is for automotive electronic application.
- 1.3 AEC-Q200 qualified, grade 1.

## 2 Explanation Of Part Numbers:



Type	Application	Size (inch)	Number of Terminals	Rated Power	Resistance (4~6 Digits)	Tolerance	Packaging
Metal Alloy Low-Resistance Resistor	Automotive Grade	●3637	4: 4 terminals	● 3=3.0W	EX: R001 = 1mΩ	D=± 0.5% F=± 1.0%	1=1,000pcs

## 3 Product Specifications:

Type	# of Terminals	Max. Rating Power	Max. Rating Current	Max. Overload Current	T.C.R. (ppm/°C)	Resistance Range (mΩ)	Operating Temperature Range
						D(±0.5%) F(±1%)	
ACM-A3637	4	3W	54.77A	122.47A	1 mΩ: ≤±75	1	-55~170°C

IE			QA		Remark IT'S NOT UNDER CONTROL FOR PDF FILE PLS NOTE THE VERSION STATED.. Do not copy without permission	Issue Dep. DATA Center.  Series No. <b>60</b>
Written	Checked	Approved	Signing			




**ACM-A3637 Metal Alloy Low-Resistance Resistor Product Specifications (Automotive Grade)**

Document No.	IE-SP-174
Released Date	2020/01/10
Page No.	2

**3.1 Power Derating Curve:**

Operating Temperature Range : - 55 ~+170 °C

For resistors operated in ambient temperatures 70°C, power rating shall be derated in accordance with the curve below:



**3.2 Rating Current:**

The following equation may be used to determine the DC (Direct Current) or AC (Alternating Current) currents (RMS, root mean square value) of normal rated power. However, if the result value exceeds the highest current of regulated standards, the highest normal rated power is to be used.

Remark:

$$I = \sqrt{P/R}$$

I=Rating Current(A)  
P= Rating Power(W)  
R=Resistance(Ω)

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE  
PLS NOTE THE VERSION STATED..

Issue Dep. DATA Center.

Do not copy without permission

Series No. **60**



**ACM-A3637 Metal Alloy Low-Resistance Resistor Product Specifications (Automotive Grade)**

Document No.

IE-SP-174


Released Date

2020/01/10

Page No.

3

**4 Physical Dimensions:**



Type	# of Terminals	Dimensions - in inches (millimeters)					
		L	W	A	B	T	H
ACM-A3637	4	0.360±0.010 (9.14±0.254)	0.370±0.010 (9.40±0.254)	0.059±0.010 (1.50±0.254)	0.039±0.010 (1.00±0.254)	0.091±0.010 (2.31±0.254)	0.047±0.010 (1.20±0.254)

**4.1 Material of Alloy**

Type	# of Terminals	Watts	Material	Resistance
ACMA3637	4	3.0	Copper-Manganese Alloy	1mΩ

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE  
PLS NOTE THE VERSION STATED..

Issue Dep. DATA Center.

Do not copy without permission

Series No. **60**



**ACM-A3637 Metal Alloy Low-Resistance Resistor Product Specifications (Automotive Grade)**

<b>Document No.</b>	<b>IE-SP-174</b>
<b>Released Date</b>	<b>2020/01/10</b>
<b>Page No.</b>	<b>4</b>

**5 Reliability Performance:**

Test Item	Conditions of Test	Test Limits							
Short Time Overload	Applied Overload for 5 seconds and release the load for about 30 minutes, then measure its resistance variance rate. (Overload condition refer to below):	$\leq \pm 0.5\%$							
	<table border="1"> <tr> <td>Type</td> <td># of Terminals</td> <td>Power (W)</td> <td># of rated power</td> </tr> <tr> <td>ACM-A3637</td> <td>4</td> <td>3.0</td> <td>5 times</td> </tr> </table> Refer to JIS C 5201-1 4.13	Type	# of Terminals	Power (W)	# of rated power	ACM-A3637	4	3.0	5 times
Type	# of Terminals	Power (W)	# of rated power						
ACM-A3637	4	3.0	5 times						
Resistance to Solder Heat	The tested resistor be immersed 25 mm/sec into molten solder of $260 \pm 5^\circ\text{C}$ for $10 \pm 1$ secs. Then the resistor is left in the room for 1 hour, and measured its resistance variance rate. Refer to MIL-STD-202 Method 210	$\leq \pm 0.5\%$ No evidence of mechanical damage							
Solderability	Add flux into tested resistors, immersion into solder bath in temperature $245 \pm 5^\circ\text{C}$ for $3 \pm 0.5$ secs. Refer to J-STD-002	Solder coverage over 95%							
Vibration	The resistor shall be mounted by its terminal leads to the supporting terminals on the solid table. The entire frequency range :from 10 Hz to 55 Hz and return to 10 Hz, shall be transferred in 1 min. Amplitude : 1.5mm This motion shall be applied for a period of 4 hours in each 3 mutually perpendicular directions (a total of 12hrs) Refer to MIL-STD-202 Method 204	$\leq \pm 0.5\%$							
		No evidence of mechanical damage							
High Temperature Exposure (Storage)	Put tested resistor in chamber under temperature $170 \pm 5^\circ\text{C}$ for 1,000 hours. Then leaving the tested resistor in room temperature for 60 minutes , and measure its resistance variance rate. Refer to MIL-STD-202 Method 108	$\leq \pm 0.5\%$							
		No evidence of mechanical damage							
Temperature Cycling (Rapid Temperature Change)	Put the tested resistor in the chamber under the temperature cycling which shown in the following table shall be repeated 1,000 times consecutively. Then leaving the tested resistor in the room temperature for 60 minutes, and measure its resistance variance rate.	$\leq \pm 0.5\%$							
		<table border="1"> <tr> <th colspan="2">Testing Condition</th> </tr> <tr> <td>Lowest Temperature</td> <td><math>-55 +0/-10^\circ\text{C}</math></td> </tr> <tr> <td>Highest Temperature</td> <td><math>150 +10/-0^\circ\text{C}</math></td> </tr> </table> Refer to JESD22 Method JA-104	Testing Condition		Lowest Temperature	$-55 +0/-10^\circ\text{C}$	Highest Temperature	$150 +10/-0^\circ\text{C}$	No evidence of mechanical damage
Testing Condition									
Lowest Temperature	$-55 +0/-10^\circ\text{C}$								
Highest Temperature	$150 +10/-0^\circ\text{C}$								
Moisture Resistance (Climatic Sequence)	Put the tested resistor in chamber and subject to 10 cycles of damp heat and without power. Each one of which consists of the steps 1 to 7 (Figure 1). Then leaving the tested resistor in room temperature for 24 hr, and measure its resistance variance rate. Refer to MIL-STD 202 Method 106	$\leq \pm 0.5\%$							
		No evidence of mechanical damage							
Bias Humidity	Put the tested resistor in chamber under $85 \pm 5^\circ\text{C}$ and $85 \pm 5\%$ RH with 10% bias and load the rated current for 90 minutes on, 30 minutes off, total 1,000 hours. Then leaving the tested resistor in room temperature for 60 minutes, and measure its resistance variance rate. Refer to MIL-STD-202 Method 103	$\leq \pm 0.5\%$							
		No evidence of mechanical damage							

Remark	<div style="border: 1px solid black; padding: 5px; display: inline-block;">           IT'S NOT UNDER CONTROL FOR PDF FILE            PLS NOTE THE VERSION STATED..         </div>	Issue Dep. DATA Center.
	Do not copy without permission	Series No. <b>60</b>



# ACM-A3637 Metal Alloy Low-Resistance Resistor Product Specifications (Automotive Grade)

Document No.	IE-SP-174
Released Date	2020/01/10
Page No.	5


Operational Life	Put the tested resistor in chamber under temperature $70 \pm 2^\circ\text{C}$ and load the rated current for 90 minutes on 30 minutes off, total 1000 hours. Then leaving the tested resistor in room temperature for 60 minutes, and measure its resistance variance rate. Refer to MIL-STD-202 Method 108	$\leq \pm 1.0\%$ No evidence of mechanical damage
------------------	---	--

## 6 Measurement Point :

Bottom electrode	Unit : mm		
	DIM	A	B
	Type	ACM- A3637-4T	6.82±0.10

## 7 Taping specifications:


### 7.1 Tape Dimensions:



Unit: mm

TYPE	DIM	Ao	Bo	W	E	F	Ko	Po	P1	P2	Do	D1
ACM-A3637-4		9.6±0.1	9.9±0.1	16.0±0.2	1.75±0.1	7.5±0.1	1.5 Max	4.0±0.1	12.0±0.1	2.0±0.1	1.5±0.1	1.5 Max

### 7.2 Lead Dimensions:



Remark

IT'S NOT UNDER CONTROL FOR PDF FILE  
PLS NOTE THE VERSION STATED..

Do not copy without permission

Issue Dep. DATA Center.

Series No. **60**



# ACM-A3637 Metal Alloy Low-Resistance Resistor Product Specifications (Automotive Grade)

Document No.

IE-SP-174

Released Date


2020/01/10

Page No.

6

### 7.3 Cover Tape Peel off Strength:


Specification value: 0.3~1.0N(30~100gf)



### 7.4 Packaging model:



Type	# of Terminals	Tape width	Max. Packaging Quantity (pcs/reel)
			Embossed Plastic Type
ACM -A3637	4	16mm	4mm pitch 1000

### 7.5 Reel Dimensions:



Reel Type / Tape	W	M	A	D
7" reel for 16 mm tape	17.4 ± 1.0	178 ± 2.0	13.2 ± 0.5	60.0 ± 1.0

### 7.6 Label:



Remark

IT'S NOT UNDER CONTROL FOR PDF FILE  
PLS NOTE THE VERSION STATED..

Issue Dep. DATA Center.


Do not copy without permission

Series No. **60**


**8 Technical application note (This is for recommendation, please customer perform adjustment according to actual application)**

**8.1 Recommend soldering method:**

8.1.1 Typical examples of soldering processes that provides reliable joints without any damage are given in below:



Recommended IR Reflow Soldering Profile



Recommended double-wave Soldering Profile


Typical values (solid line)

Process limits (dotted line)

8.1.2 Soldering Iron: temperature  $350^{\circ}\text{C} \pm 10^{\circ}\text{C}$ , dwell time shall be less than 3 sec.

**8.2 Recommend Land Pattern:**

When a component is soldered, the resistance after soldering changes slightly depending on the size of the soldering area and the amount of soldering. When designing a circuit, it is necessary to consider the effect of a decrease or increase in its resistance



Type	# of Terminals	Maximum Power Rating (Watts)	Resistance Range (mΩ)	Dimensions - in millimeters				
				a	b	c	d	i
ACM-A3637	4	3	1	2.95	9.90	1.68	0.60	4.50

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE  
PLS NOTE THE VERSION STATED..

Issue Dep. DATA Center.

Do not copy without permission

Series No. **60**



**ACM-A3637 Metal Alloy Low-Resistance Resistor Product Specifications (Automotive Grade)**

Document No.	IE-SP-174
Released Date	2020/01/10
Page No.	8

**8.3 Automobile Electronic Application:**

This specification is for automobile electronic use. RALEC will take no responsibility if any damage, cost or loss occurs when the product has been used in any special circumstances.

**8.4 Environment Precautions:**

If consumer intends to use our company product in special environment or condition (including but not limited to those mentioned below), then will need to make individual recognition of product features and reliability accordingly.

- (a) Used in high temperature and humidity environment
- (b) Exposed to sea breeze or other corrosive gas, such as Cl<sub>2</sub>、H<sub>2</sub>S、NH<sub>3</sub>、SO<sub>2</sub> and NO<sub>2</sub>.
- (c) Used in non-verified liquids including water, oil, chemical and organic solvents.
- (d) Using non-verified resin or other coating material to seal or coat our Company product.
- (e) After soldering, it is necessary to use water-soluble detergents to clean residual solder fluxes, even though no-clean fluxes are recommended.

**8.5 Momentary Overload Precautions:**

The product might be out of function when momentary overloaded. Please make sure to avoid momentary overloading while using and preserving ◦

**8.6 Operation and Processing Precautions:**

- (a) Avoid damage to the edge of resistor and protective layer caused by mechanical stress.
- (b) Handle with care when printing circuit board (PCB) is divided or fixed on support body, because bending of printing circuit board (PCB) mounting will make mechanical stress for resistors.
- (c) Make sure the power rating is under the limit when using the resistor. When power rating is over the limit, the resistor will be overloaded. There might be machinery damage due to the climbing temperature.
- (d) If the resistor will be exposed under massive impact load (shock wave) in a short period of time, the working environment must be set up well before use.
- (e) Please make evaluation and confirmation when the product is well used in your company and have a through consideration of it's fail-safe design to ensure the system safety.

**9 Storage and transportation requirement:**

9.1 The temperature condition must be controlled at 25±5℃, the R.H. must be controlled at 60±15%. The stock can maintain quality level in two years ◦

Remark	IT'S NOT UNDER CONTROL FOR PDF FILE PLS NOTE THE VERSION STATED..	Issue Dep. DATA Center.
	Do not copy without permission	Series No. <b>60</b>





**ACM-A3637 Metal Alloy Low-Resistance Resistor Product Specifications (Automotive Grade)**

Document No.	IE-SP-174
Released Date	2020/01/10
Page No.	9

9.2 Please avoid the mentioned harsh environment below when storing to ensure product performance and its' weldability. Places exposed to sea breeze or other corrosive gas, such as Cl<sub>2</sub>、H<sub>2</sub>S、NH<sub>3</sub>、SO<sub>2</sub> and NO<sub>2</sub>.

9.3 When the product is moved and stored, please ensure the correct orientation of the box. Do not drop or squeeze the box. Otherwise, the electrode or the body of the product may be damaged.

**10 Attachments**

10.1 Document Revise Record (QA-QR-027)

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE  
PLS NOTE THE VERSION STATED..

Issue Dep. DATA Center.

Do not copy without permission

Series No. **60**



**LR-A3637 Metal Alloy Low-Resistance Resistor Product Specifications (Automotive Grade)**

Document No.	IE-SP-174
Released Date	2020/01/10
Page No.	10

**Legal disclaimer**

RALEC, its distributors and agents (collectively, "RALEC"), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. RALEC may make changes, modifications and/or improvements to product related information at any time and without notice.

RALEC makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, RALEC disclaims (i) any and all liability arising out of the application or use of any RALEC product, (ii) any and all liability, including without limitation liability for any loss of profits or for direct, indirect, special, punitive, consequential or incidental damages arising out of or related to RALEC products, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability.

RALEC defined this product is for automotive electronic use , not design for any application for medical life-saving or life support equipment, or any application which may inflict casualties if RALEC product failure occurred. Any and all technical advice furnished by RALEC with reference to the use of RALEC products are given free of charge and RALEC assumes no obligation or liability for the advice given or results obtained, and all such advice are given and accepted at buyer's risk. Buyer shall assume all risk and liability for the results obtained by the use of any RALEC products in combination with other articles or material or in the practice of any process, regardless of any oral or written technical statement made by RALEC with respect to the use of such products by way of technical advice or otherwise. Further, buyer represents and warrants that it has the experience and capacity of determining the correct product for its intended application.

Information provided here is intended to indicate product specifications only. RALEC reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by ECN.

Remark	IT'S NOT UNDER CONTROL FOR PDF FILE PLS NOTE THE VERSION STATED..	Issue Dep. <b>DATA Center.</b>
	Do not copy without permission	Series No. <b>60</b>